EzyJamb

EZC | Classic Adjust Door Frame



EzyJamb

EZC | Classic Adjust Door Frame

EzyJamb® Classic Adjust - EZC is a split type door jamb system that creates inconspicuous clean lines to complete the contemporary look of architectural spaces. The two-piece jamb is made specific to your wall throat, yet has 3/8" +/- field adjustments to allow for inconsistencies at install.



Product Details

EZYJAMB EZC CLASSIC ADJUST DOOR FRAME FOR 1-3/8 (EZa) AND 1-3/4 (EZc) DOORS

Material	20ga Galvanneal	
Min / Max Width	10" / 3'-0" (Single) 20" / 6-0' (Double)	*(Custom sizes available on request)*
Min / Max Height	24" / 8-0'	*(Custom sizes available on request)*
Wall Throat	3-1/2" - 8-7/8"	*(Custom sizes available on request)*
Fire Rating	90 minutes - Up to 3080 single, 6080 double	*(EZa | 1-3/8" is not Fire Rated)*
Hinge Options	1 Concealed Hinges 2 Mortise Hinges 3 Non-Mortise Hinges	



Preparation Options

EZa | 1-3/8”



Strike Options	T-Strike DeadBolt PLS 24
Hinge Options	Non-Mortise Hinge RYST-60

EZc | 1-3/4”



Strike Options	T-Strike ASA Strike DeadBolt Rim Reinforcement	NoHa Flushbolt PLS 24 T Strike Roller Latch (Short Lip)
Hinge Options	Non-Mortise Hinge 4” Standard Weight Mortise Hinge RYST-60 / RYST-80 Tectus 340 SOSS 216 /416	
Closer Options	RocYork Surface Closer PA Reinforcement Surface OH Stop	

Specification Details

- Frame Type
- Door Thickness
- Frame Width
- Frame Height
- Finished Wall Thickness
- Fire Rating
- Strike Type
- Strike Height
- Frame Handing
- Hinge Type
- Hinge Quantity

EX . EZc - 1.75 - 3-0’ - 7-0’ - 4-7/8 - 20MIN - ASA-38” - RH - RYST80 - 3

Availability

- All EzyJamb, CavKit and SlideSet products are made to order.
- Lead times apply to all EzyJamb, CavKit and SlideSet orders. Always confirm exact lead time with EZ Concept prior to placing order.
- All orders are accepted by EZ Concept on a FIFO basis (first in, first out). For urgent orders, please refer to the point below.

Expedited Orders

- For urgent orders, manufacturing processes can be expedited on request.
- Expedition of EzyJamb, Cased Openings, CavKit and SlideSet orders is not always possible and is subject to operational requirements. Always confirm exact lead time with EZ Concept prior to placing order.

Custom Door Sizes

- Custom size EzyJamb, CavKit and SlideSet products are available on request. Longer lead times and additional charges may apply for custom sizes. Custom latch plate punching is available on request.

North America Door Handing



Hand all doors by standing outside and facing the door.

Installation Instructions

Step 1

Refer to Rough Opening guide (pages 22, 23)

Ensure that the **stud opening** is square and level and is the correct size.

Make sure the rough opening has double studs, the manufacturer strongly recommends wood studs or a minimum 18 gauge .030 metal studs on both sides of the opening. Studco recommends double studs for this installation.

When using concealed hinges, the stud must be **notched** at each hinge location to ensure proper fitment.





Step 2

Fasten hinge side first, making sure jamb is level and as tight against stud opening as possible. Then screw at 8" centers up stile, screwing back through drywall into stud jamb. See *Detail 'B'* and *'C'*.

Double screw all ends as *Detail 'D'* and beside hinge position - both above and below hinge if using concealed hinges as *Detail 'E'*.





Step 2A | Head Installation



Head joiners as inserted in jamb.



Locate head into joiner and make flush with jamb so the head joiner is not seen.



Remove the remaining head joiner out of the strike jamb into the end of the head (as shown) to receive the strike jamb.

Installation Instructions

Step 3

Fasten the final vertical section (strike jamb) below the head section. Ensure that the spacing between the two vertical sections are spaced evenly at the required distance.

Install door prior to mudding to ensure proper tolerances, then disassemble and reinstall after mudding.



Step 4

Ensure the perforated side strips sit flat against the drywall to enable the jamb sections to be easily set into the wall surface. Finish the jamb with drywall compound.

All the corners must be paper taped and mudded in as Detail 'F'.

Hang the door in position leaving 1/8" clearance from the top and the hinged side using the EzyJamb Standard or Invisible Hinges. Install the striker plate into position to align with the latch plate punching.





Completed Installation

The completed jamb is flush finished and can be painted in with the whole wall area to fully conceal any fixing, achieving simple clean lines around the door face.

For further information or assistance in installation of EzyJamb products, please visit:

https://ezconcept.com.au/resources/installation-instructions/

For Sales and Technical Enquiries, please contact EZ Concept USA.

T: 1 888 399 5262
W: www.ezconcept.com
E: sales@ezconcept.com

Head Office - Rochester
1700 Boulter Industrial Parkway,
Webster, NY 14580